



Specifications

| MODELS | GR-12 | | GR-15 | | GR-20 | |
|--|---------------|--------------|---------------|--------------|---------------|--------------|
| | Metric | US | Metric | US | Metric | US |
| Working Height | 5.48 m | 17 ft 5 in | 6.47 m | 20 ft 8 in | 8.07 m | 25 ft 11 in |
| Platform Height | 3.48 m | 11 ft 5 in | 4.47 m | 14 ft 8 in | 6.07 m | 19 ft 11 in |
| A Height (stowed) | 1.57 m | 5 ft 2 in | 1.57 m | 5 ft 2 in | 1.98 m | 6 ft 6 in |
| B Length (stowed) | 1.35 m | 4 ft 5 in | 1.35 m | 4 ft 5 in | 1.35 m | 4 ft 5 in |
| C Width | 75 cm | 75 cm | 2 ft 5.5 in | 80 cm | 2 ft 7.5 in | |
| D E Platform Dimensions (l x w) | | | | | | |
| Standard platform | 88 x 75 cm | 35 x 29.5 in | 88 x 75 cm | 35 x 29.5 in | 88 x 75 cm | 35 x 29.5 in |
| Standard platform with extension | 1.4 m x 75 cm | 55 x 29.5 in | 1.4 m x 75 cm | 55 x 29.5 in | 1.4 m x 75 cm | 55 x 29.5 in |
| Stock Picker platform | 88 x 73 cm | 35 x 28.8 in | 88 x 73 cm | 35 x 28.8 in | 88 x 73 cm | 35 x 28.8 in |
| Stock Picker platform with adjustable tray | 1.4 m x 73 cm | 56 x 28.8 in | 1.4 m x 73 cm | 56 x 28.8 in | 1.4 m x 73 cm | 56 x 28.8 in |
| Standard AWP platform | 69 x 51 cm | 27 x 26 in | 69 x 51 cm | 27 x 26 in | 69 x 51 cm | 27 x 26 in |
| Narrow AWP platform | 66 x 51 cm | 26 x 20 in | 66 x 51 cm | 26 x 20 in | 66 x 51 cm | 26 x 20 in |
| Standard fibreglass platform | 74 x 67 cm | 29 x 26.5 in | 74 x 67 cm | 29 x 26.5 in | 74 x 67 cm | 29 x 26.5 in |
| Narrow fibreglass platform | 66 x 56 cm | 26 x 22 in | 66 x 56 cm | 26 x 22 in | 66 x 56 cm | 26 x 22 in |

| PRODUCTIVITY | | | | | | |
|-----------------------|----------------------------|---------|----------------------------|---------|----------------------------|---------|
| Lift Capacity | 227 kg | 500 lbs | 227 kg | 500 lbs | 159 kg | 350 lbs |
| Ground Clearance | 6.35 cm | 2.5 in | 6.35 cm | 2.5 in | 6.35 cm | 2.5 in |
| Drive Speed (stowed) | 4.0 km/h | 2.5 mph | 4.0 km/h | 2.5 mph | 4.0 km/h | 2.5 mph |
| Drive Speed (raised) | 0.8 km/h | 0.5 mph | 0.8 km/h | 0.5 mph | 0.8 km/h | 0.5 mph |
| Gradeability* | 30% | 30% | 30% | 30% | 30% | 30% |
| Turning Radius-inside | Zero | Zero | Zero | Zero | Zero | Zero |
| Controls | 12 V proportional controls | | 12 V proportional controls | | 12 V proportional controls | |
| Tyres | Non-marking tyres | | Non-marking tyres | | Non-marking tyres | |

| POWER | | | | | | |
|---------------------------|-----------------------------------|---------|-----------------------------------|---------|-----------------------------------|---------|
| Power Source | 4 batteries, 6 V 225 Ah batteries | | 4 batteries, 6 V 225 Ah batteries | | 4 batteries, 6 V 225 Ah batteries | |
| Hydraulic System Capacity | 8.33 L | 2.2 gal | 8.33 L | 2.2 gal | 8.33 L | 2.2 gal |

| WEIGHT | | | | | | |
|----------|--------|-----------|--------|-----------|----------|-----------|
| Weight** | 717 kg | 1,581 lbs | 994 kg | 2,192 lbs | 1,111 kg | 2,451 lbs |

| WEIGHT | | | | | | |
|-------------------------------------|--|--|--|--|--|--|
| CE Compliance option | | | | | | |
| Fully certified load sensor (EN280) | | | | | | |
| AS 1418.10 | | | | | | |

*Gradeability applies to driving on slopes. See operators manual for details regarding slope rating.

**Weight will vary depending on options and/or country standards.

Features

STANDARD FEATURES

MEASUREMENTS

GR-12

- 5.48 m (17 ft 5 in) working height
- 3.48 m (11 ft 5 in) platform height
- 1.57 m (5 ft 2 in) stowed height
- 1.35 m (4 ft 5 in) stowed length
- 75 cm (2ft 5.5 in) width

GR-15

- 6.47 m (20 ft 8 in) working height
- 4.47 m (14 ft 8 in) platform height
- 1.57 m (5 ft 2 in) stowed height
- 1.35 m (4 ft 5 in) stowed length
- 75 cm (2ft 5.5 in) width

GR-20

- 8.07 m (25 ft 11 in) working height
- 6.07 m (19 ft 11 in) platform height
- 1.98 m (6 ft 6 in) stowed height
- 1.35 m (4 ft 5 in) stowed length
- 80 cm (2ft 7.5 in) width

PRODUCTIVITY

- High strength aluminium rigid mast system
- Narrow 75 cm to 80 cm width and 1.35 m length
- Low 38 cm entry height
- On-board diagnostics and battery indicator
- Proportional drive and lift controls
- Maximum manoeuvrability steering system
- Alarm system and flashing beacon



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Stock picker platform with adjustable tray
- Extension platform
- Maintenance-free battery
- Automotive horn
- Fluorescent tube caddy

POWER

- Power wheel assist with dual battery package
- Dual battery package

Genie Australia

591 Boundary Road, Darra, Qld 4076
PO Box 394, Richlands, Qld 4077
Tel: + 61 7 3375 1660
Toll Free In Australia: 1800 331 660
Fax: + 61 7 3375 1002

European Offices

UK

The Maltings
Wharf Road
Grantham NG31 6BH
UK
Tel: +44 (0)1476 584333
Fax: +44 (0)1476 584334

France

10, ZA de la Croix St. Mathieu
28320 Gallardon
France
Tel: +33 (0)2 37 26 09 99
Fax: +33 (0)2 37 26 09 98

Germany

Finienweg 3
28832 Achim/Bremen
Germany
Tel: +49 (0)4202 8852-0
Fax: +49 (0)4202 8852-25

Spain

Gai`a 31, Pol. Ind. Pl`a d'en Coll
08110 Montcada i Reixac
Barcelona
Spain
Tel: +34 93 572 50 90
Fax: +34 93 572 50 91

Scandinavia

Tagenevägen 72
425 37 Hisings Kärra
Sweden
Tel: +46 31 57 51 00
Fax: +46 31 57 90 20

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730
USA
Tel: +1 425 881-1800
Fax: +1 425 883-3475

WEB: www.genieindustries.com.au

Distributed By: