

nifty

TrackDrive

TRACK MOUNTED ACCESS PLATFORM

9m, 12m & 17m

Working heights

Superb Gradeability

Will climb very steep
inclines as high as 60% (31°)

Excellent Traction

Better grip on uneven terrain

Fully Proportional Hydraulic Controls

Ergonomic & reliable

Weight Saving Design

Lower cost transportation and
better fuel economy on site

Non-Marking Tracks

Optional rubber-free tracks
available for indoor usage

Variable Width Tracks

Access to narrow openings
improving versatility



nifty



niftylift

TrackDrive

With working heights of 9.70m, 12.20m and 17.10m, Nifty's new TrackDrive platforms offer a range of capabilities to suit operator requirements. The TD90 is a compact and manoeuvrable machine capable of passing through a 0.75m opening making it the ideal tool for jobs where space is limited. The TD120T is available in two versions, the standard and narrow width machines. The standard version offering a wider track width for steeper or rougher terrain and the narrow version will pass through a 0.75m opening for restricted access. The TD170 provides an impressive working envelope and its TrackDrive base allows it to travel over ground where even a 4WD SP platform would have difficulty finding traction.



TD170



TD120T



TD90

Weight saving designs mean that site-to-site transportation is more economical. The platforms are also more efficient, allowing them to work for longer while using less fuel.

Also available are rubber-free urethane tracks. Ideal for internal or clean applications, these tracks will increase the number of locations that the TrackDrives can work, greatly improving their utilisation



Specifications	TD90	TD120TN	TD120T	TD170
Height - Working	9.70m	12.20m	12.20m	17.10m
Height - Platform	7.70m	10.20m	10.20m	15.10m
Outreach - Working	3.50m	6.10m	6.10m	8.70m
Slew	355°	406°	406°	355°
Width - Travelling	0.75m	0.75m - 1.15m	1.10m - 1.50m	1.85m
Width - Working	2.10m	2.93m	3.55m	4.37m
Height - Stowed	1.90m	1.90m	1.90m	2.10m
Length	3.70m	3.95m	3.95m	5.60m
Weight	850kg	1770kg	1650kg - 1850kg	2900kg
Platform Capacity	120kg	120kg	200kg	200kg
Platform Size	0.60m x 0.60m	0.75m x 0.65m	1.10m x 0.65m	1.10m x 0.65m
Drive Speed	1.3 - 2.1mph	0.6 - 1.0mph	0.6 - 1.0mph	0.6 - 1.0mph
Gradeability	30%	60%	60%	32%
Control System	Fully proportional hydraulic			

Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.