

Organisation	RAR Cranes Australia Pty Ltd Contact		Andrew Bodman
ABN	53 629 970 252	Contact Position	Director
Address	38 Bedford St, Queanbeyan, NSW 2620	Contact Phone	02 6299 6100

Project Details	Detailed RAR Site Specific Job Docket	Supervisor	
Activity	Lifting Mechanical and Electrical Plant	Position	Crane Operator
Resources	Crane Driver/Dogman/Rigger		

Plant	Crane detailed on RAR Job Docket					
PPE Required		Injuries and Incidents	All injuries and Incidents are to be reported to Head Contractor and RAR Management			

Maintenance	Every 250 hours as per manufacturers specification, Daily Pre-Start checklists					
Materials Involved	Plant, Chains, slings, timber, lifting equipment.					
SWMS Review	SWMS are monitored and reviewed annually or as required. Amended only after consultation with RAR staff and Safety Advisor					

Emergency Procedures					
Plant Mechanical Failure	Plant Collision/Rollover				
1. Shut down plant	1. If any injuries, call 000				
2. Isolate plant	2. Direct emergency services to site				
3. Notify RAR and Site Manager	Contact First Aid – Two Way/Nurse Call/Verbal				
4. Implement lockout for Repair	4. Isolate the area				
	5. Notify RAR and Site Manager				

This SWMS has been developed in consultation with all RAR Employees RAR Crane Safety Plan, Crane Compliance paperwork, Insurances and SWMS are available at <u>www.rargroup.com.au/ohs</u>						
Sign Off WHSE Coordinator Contact No Date						
(Je	Dick Garrety	0405 991 935	15/04/2023			



Legal Information

Legislation						
A.C.T	N.S.W					
Work Health & Safety Act 2011 (effective 03/09/20)	Work Health and Safety Act 2011					
Work Health & Safety Regulations 2011 (effective 03/08/20)	Work Health and Safety Regulations 2019					
Workers Compensation Act 1951	Workers compensation Act No 70 1987					
Machinery Act (1949)	Workers Compensation Regulations 2016					
Machinery Regulations (1950)						
Codes of Practice						
A.C.T	N.S.W					
Construction Work 2018	Construction Work 2019					
How to Manage Work Health and Safety Risks 2020	How to Manage Work Health and Safety Risks 2019					
Managing Risks of Plant in the Workplace 2020	Managing the Risks of Plant in the Workplace 2019					
Hazardous Manual Tasks 2020	Hazardous Manual Tasks 2019					
Work Health and Safety Consultation Cooperation Coordination 2018	Work Health and Safety Consultation Cooperation Coordination 2019					
Managing Noise and Preventing Hearing Loss at Workplaces 2020	Managing Noise and Preventing Hearing Loss at Work 2019					
Managing the Work Environment and Facilities 2020	Managing the Work Environment and Facilities 2019					
Managing Risks of Falls at Workplaces 2020	Managing the risk of falls at workplaces 2019					
National Code of Practice for Precast Tilt-Up and Concrete Elements in Building	Construction 2008					
Industry Guidelines						
CICA Crane Safety Manual						
Australian Standards						
AS/NZS ISO 31000 Risk Management – 2018						
AS 2550.1 Cranes, hoists and winches - Safe use General requirements - 2011						
AS 2550.5 Cranes, hoists and winches - Safe use Mobile cranes - 2016						
AS 3850.1 Prefabricated -General requirements (amendment 1:2019)						
AS 3775.2 Chain slings for lifting purposes - Grade T(80) and V(100) Care and us	e - 2014					
AS 1353.2 Flat synthetic-webbing slings Care and use – 1997 (R2014)						
AS 4497.2 Roundslings - Synthetic fibre Care and use - 2018						
AS 2741 Shackles – 2002 (R2014)						
AS/NZS 2161.1 Occupational protective gloves Selection, use and maintenance	- 2016					
AS 1319 Safety signs for the occupational environment - 1994						



High Risk Activity Identification

Item No	High Risk Activity	Applies to Project?
1	Require High Risk Licence	Yes
2	Is carried out at an area in a work place in which there is any movement of powered plant	Yes
3	Involves a risk of a person falling more than 2 meters	Yes
4	Is carried out on a telecommunication Tower	No
5	Involves the demolition of an element of a structure that is load bearing or otherwise related to the physical integrity of the structure	No
6	Involves or is likely to involve the disturbance of asbestos	No
7	Involves structural alterations or repairs that require temporary support to prevent collapse	No
8	Is carried out in or near a confined space	No
9	Is carried out in or near existing residential building	Yes
10	A shaft or trench with an excavated depth of more than 1.5 meters	Yes
11	A tunnel	No
12	Involves the use of explosives	No
13	Is carried out on or near pressurized gas distribution mains or piping	No
14	Is carried out on or near chemical, fuel or refrigeration lines	No
15	Is carried out on or near energized electrical installations or services	Yes
16	Is carried out in an area that may have a contaminated or flammable atmosphere	No
17	Involves Tilt up or pre-Cast Concrete	No
18	Is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor that is in use by traffic other than pedestrians.	Yes
19	Is carried out in an area in which there are artificial extremes of temperature	No
20	Is carried out in or near water or other liquid that involves a risk of drowning	No
21	Involves diving work	No
22	Involves the cutting of crystalline silica material using a power tool or mechanical process	No



The RAR CLEAR Priciples are to be used for Every Lift:

Communication

- Radio is working or you are in view of the driver
- Give clear and precise directions

Lifting gear is appropriate for the lift

- Chains/slings/shackles et. Are rated for the lift
- Chain size, Angle factor and Reeve factors considered
- All lifting gear is inspected before use

Every load is inspected 360 degrees before lifting

- Check position and bite of chains/slings and look for loose items
- Come up slowly on the hook until clear of all obstructions

Area of work area is clear

• Check for – Public/other workers, Vehicles/plant, Powerlines, Scaffold, Trees

 ${f R}$ echeck under load for loose items before going above head height

If you have any concerns about a lift STOP immediately. Clear the area and bring the load back to the ground. If issue cannot be resolved call your supervisor

Authorised: Andrew Bodman Released: 17.4.23 Doc ID: RAR-WHSE-10-B



Consequences: How severely can it hurt someone?									
Likelihood: How likely is it to happen	Minor	Moderate	Major	Extreme	Consequence Definitions				
Very Likely	7 Medium	11 Medium	14 High	16 High	Extreme Single or multiple fatality, Critical incident for business, over \$100,000 business loss				
Likely	4 Low	8 Medium	12 Medium	15 High	Major		ith some weeks off work (e. eye etc), over \$50,000 busir		-
Unlikely	2 Low	5 Low	9 Medium	13 Medium	Moderate Considerable injury (e.g. major cut/graze, stitches, crushed finge etc), over \$10,000 business loss			nger	
Very Unlikely	1 Low	3 Low	6 Low	10 Medium	Minor Minor injury (e.g. cut finger requiring band-aid, small graze etc), minimal to no business loss				tc),
Likelihood Definition	ikelihood Definitions					MANAGE	MENT		
Vory Likoly	Constant exposure to the hazard, easily foreseeable, could happen any moment, has happened on several occasions								
	egular exposure t ccurred before	to the hazard,	could happen a	at times, has		HIGHEST	Level 1	MOST	
Unlikely	frequent exposu as occurred once			en but not likel	γ ,	tion	Eliminate the hazards	SS SS	
Very Unlikely	arely exposed to eard of it happen		t really expect	ed, have never		ety protection	Level 2 Substitute the hazard with something safer	ol measures	
	Risk	Treatment				nd saf	Isolate the hazard from people	control	
					d	health and safety	Reduce the risks through engineering controls	Reliability of	
	To be further controlled as reasonably practicable. Work can proceed with supervision and approval from the supervisor					Level of	Level 3 Reduce exposure to the hazard using	S S S S S S S S S S S S S S S S S S S	
A C	To be controlled as per standard works e.g. SWMS and chosen controls. Ongoing monitoring by workers / supervisors.				1	LOWEST	administrative actions	LEAST	

CODE OF PRACTICE | HOW TO MANAGE WORK HEALTH AND SAFETY RISKS



Risk Assessments

ltem No.	Task	Task Hazards/Risks Initial Risk Controls Rating		Residual Risk Rating	Responsibility	
		Setting up in the wrong location	14	Eliminate - Head contractors to be contacted before entering onto site to confirm set up location.	9	Crane Crew
		Personnel and Plant not site compliant	11	Admin – Complete Head Contractor Site Induction and Plant Compliance paperwork before commencing work.	3	Crane Crew
1	Arrive on site	Crushing of pedestrian	14	Engineer – Dogman to exit crane and act as spotter when crane is moving on site. Orange flashing light/s operational when moving onsite and reversing beeper to be in operation when reversing.	9	Crane Crew
		Injury due to tripping over materials on the ground	11	PPE – Ankle high, lace up Safety Boots to be always worn when outside crane cab.	3	Crane Crew
		Being struck by plant	14	PPE - Hi Visibility clothing to be worn at all times.	9	Crane Crew



HRSWMS No. 8 Revision 8

		Potential exposure to airborne contaminants	11	 Admin – Visually inspect work site activities and assess tasks that may create dust/airborne contaminants. Isolation – <u>DO NOT</u> conduct works in an area where airborne contaminants or Silica dust are being generated. If other site trades are not controlling their hazards report it to the site supervisor. Admin – Notify site safety team & RAR management if activities are deemed unsafe due to potential contact with airborne contaminants. 	5	Crane Crew
2	Complete Pre-Start Daily Checklist for crane.	Crane not operating as per manufactures specifications.	14	Engineer - Complete Daily Operator Checks on Crane and Lifting Gear each morning before commencing work and fill in Daily Operator Checklist. If a safety malfunction is identified, equipment is not to be operated and Lock Out fitted. Head Contractor to be notified of Lock Outs.	9	Crane Driver
3	Complete RAR Site Specific Risk Assessment and Toolbox Talk.	Crane not setting up in suitable area or in suitable conditions.	14	Isolate - Before setting up crane complete RAR Site Specific Risk Assessment & Toolbox Talk on the RAR Site Specific Job Docket. Consult with crew and Head Contractor Forman and ask all participants to sign off before commencing works. This Risk Assessment asks the crew and foreman to consider the risks associated with setting up a crane on site, before it is set up.	9	Crane Crew
4	Set up crane		14	Admin - Complete all steps in RAR SWMS No.1 Crane Setup/Pack up.	9	Crane Crew



HRSWMS No. 8 Revision 8

		Load falling	14	 Engineer - Only qualified Dogman to hook up a load and direct the crane. Ensure all loads are secured to prevent risk of item falling. If unsure of how to sling the load, ask questions of other RAR employees and your supervisor. Always complete a test lift if unsure 	9	Crane Crew
5	5 Hooking up loads	Lifting gear / Plant failure	14	 Engineer - Use correct sized lifting gear for the load being lifted. Choke load whenever possible. Engineer - Refer to and follow manufacturer's instructions and specifications. Consult crane load charts to verify that the crane has the necessary rated capacity and design classification prior to carrying out any lift. If weight of item is unknown complete a test lift. If load cannot be lifted within the SWL of the crane at that radius, <u>stop the lift</u> and complete a lift study to determine correct crane for lift. 	9	Crane Crew
6	Lifting precast concrete elements	Precast Panels - Concrete elements falling	14	 Isolate - Ensure that work area has no unauthorised people in it. If you are unhappy with the work area speak to the customer about controlling or barricading the area. Admin Pre-cast Panel 'Birth Certificate' must be on site (head contractor) and presented upon dogman/riggers request. Use lifting diagram when available. Engineer - Check swift lift lugs and/or clutches are secure and are the correct size. 	9	Crane Crew



HRSWMS No. 8 Revision 8

		Road Barriers – barrier falling	14	 Engineer - Check swift lift lugs and/or clutches are secure and are the correct size. Admin – Check condition of lifting lug is good. If unsure of the condition use chains to choke the load. 	9	Crane Crew
		Misc. concrete items – item falling	14	 Engineer - Lifting equipment must be of adequate size for the weight of the item being lifted. Use lifting diagram where available. Admin - Calculate approx. weight of concrete block (Concrete weighs approximately 2500kg/m3). Operator to be informed of calculated load weight and ensure load is within chart with an additional 30% safety factor included. Engineer - Carry out test lift to ensure item is not too heavy and item is slung appropriately. If in any doubt with the lifting configuration, STOP and ask your supervisor. 	9	Crane Crew
7	Rotating precast concrete panels	Precast panel falling	14	 Isolate – Instate exclusion zones at rotation location (allow an additional 20% of the panel height) Engineer – Ensure all safety devices are working on the crane (both anti two-blocks). Ensure the crane is correctly configured to use both winches (see operators manual). Admin – The person in charge of rotation/dual crane lift must hold an Intermediate Riggers ticket. Engineer – Check all lifting clutches are engaged correctly and facing the correct way. 	9	Crane Crew

Authorised: Andrew Bodman Released: 17.4.23 Doc ID: RAR-WHSE-10-B



HRSWMS No. 8 Revision 8

8	Landing loads	Slips, trips and falls Collapse of landing area	14	 Isolate - Ensure landing area is suitable for landing the load and make sure it is clear of trip hazards. Once load has been landed ensure no items are protruding from load. Engineer - Ensure landing area is capable of carrying the weight of the item being landed. Spread loads to avoid point loading. After unhooking load continue to communicate with the crane driver and watch chains until clear of any obstructions. If in doubt ask your supervisor and the site staff 	9	Crane Crew
		Precast panel falling	14	Admin – The rigging company that is installing the precast panels are responsible for notifying the dogman of when to release the load. Before dropping any weight of a precast panel take advice from the rigging crew.	9	Crane Crew

SWMS Review

SWMS Implemented	15/04/2023		
Last Review Date	17.4.23 R-8		
Person Conducting Review	Andrew Bodman / Dick Garrety		
Position	WHSE Coordinator		



Qualifications

Qualifications required to carry out the task?	Who is required to have the qualification?	When will this be done?	
Safety Advisor	Safety advisor is responsible for the implementation and induction into the SWMS	Prior to work commencing and ongoing by workplace audits and site inspections.	
Construction Induction Card. (White Card)	All workers	Prior to commencing work	
Asbestos awareness card	All workers	Prior to commencing work	
Silica awareness training	All workers	Prior to commencing work	
Dogging High Risk License	Dogman	Prior to commencing work	
Rigging High Risk License	Riggers	Prior to commencing work.	
Crane Operator High Risk License	Crane Operators, all classes	Prior to commencing work.	
RAR Group Induction	All RAR employees	Prior to commencing work	



By signing below I confirm that:

- 1. I confirm that I have a copy of this SWMS on my phone (Employment Hero)
- 2. The SWMS and relevant Legislation /Codes of Practice to this task has been explained to me
- 3. I fully understand this SWMS and I have been consulted in the preparation of this SWMS
- 4. My qualifications are current, and I am competent to undertake this activity
- 5. I will comply with the SWMS otherwise I will stop work immediately
- 6. I will alert my supervisor if I believe I am not trained adequately to undertake any tasks

Site risk assessments may require SWMS to be amended to suit the task and conditions, this will be done in consultation with RAR crane crews, site management and RAR WHSE Coordinator. Induction into RAR SWMS was conducted by Dick Garrety.

Name	Date	Signature	Name	Date	Signature
Adam Smith			Christian Carnall		
Andrew Bell			Daniel Green		
Angus Dunlop			Darren Bailey		
Anthony Pidcock			Dean Zammit		
Ashley Charnock			Edward Gomez		
Blaine Lawler			Edward Taungakava		
Bradley Cotterill			Edward Vicente		
Brendon Kelly			Evan Steele		
Brett Leape			Geoffrey Ryan		
Brett Scarman			Glen Turner		
Ilifeleti Folauhola			Rebecca Quinn		



HRSWMS No. 8 Revision 8

Name	Date	Signature	Name	Date	Signature
Jayden Hately			Robert Morrison		
Jesse Caridi			Sheldon Van Der Kley		
Joel Newton			Simon Condon		
Justin Bennett			Stephen McCarter		
Karl Davies			Stuart Burgoyne		
Luke Johnson			Tayla Bennett		
Luke Rukavina			Timothy Blayden		
Madeleine Ashton			Troy Stratton		
Mark Solomon			Trent Jones		
Mathew Rukavina			Vedran Juretic		
Michael Cole			William Lueckhof		
Michael Hajdarovic			Zac Miller		
Mitchell Barnes					
Mitchell Williams			Graeme Gold		
Paul Tasker			Keni Kawaleva		
Raul Abell			Mathew Lewis		

Authorised: Andrew Bodman Released: 17.4.23 Doc ID: RAR-WHSE-10-B