



AT-40 Crane Service Schedule

	Service Scriedule
Date: <u>23-7-25</u> Job No.:	Tech. Name: Christian. C
Serial No.: 400049	Service Type: 1,000 hr
Owner's Details:	
Job Location: QBN YARD	
Make Of Equipment: FRANNA	Model: <u>AT - 40</u> Serial No.: 949
Registration / Plant No.: メロフスビ	Model: Serial No.: Vehicle Klms: 6538 Hours: 57951
registration / Flant No. AQ TIRE	verificie ruins. 03.56 riours. 3-75 f
Note: ALL items MUST be "Ticked" if carried out /	"Crossed" if not carried out / marked "N/A" if not applicable.
R = Repair C = Completed	
R C 250 / 750 Hour Service Schedule	Comments
CABIN & CONTROLS	
Check for EMERGENCY Steer Pump Errors	Self Test
Check Air Conditioning & Condition of Cabin Filter	Clean/replace filter if required
Check 2/4WD & HI/LO Operation	
Check Diff Lock Operation	
Check Holding Brake Operation	
Check All Emergency Stop Button Operation	
Check Reversing and Winch Camera Operation	
Check AM/FM Radio Operation	
Check Heater Operation	
Check Wiper Operation	
Refill Windscreen Washer Water & Test Operation	
Check Front Spring Lockout Operation	200 bar activation pressure
Check Park Brake Operation	255 dar adition prossure
Check Foot Valve Operation	
Check ALL Warning Lights and Buzzers	
Check ALL Instruments for Operation/Illumination	
Check Indicators	
Check Hazard Lights	
+1	
Check Horn(s)	Prince Occupate Manual for Province
Check Hyd. Sys. Base Pressure Check Hyd. Sys. Max Pressure	Refer Operator Manual for Pressures
 	Refer Operator Manual for Pressures
Check Steer Pressure at Full Lock	Refer Operator Manual for Pressures
Check Articulation Sensor Operation	
Check ALL Hydraulics for Correct Operation	
Check Joystick Operation	
Check Clearance Lights	
Check Head Lights HI/LO	
Check Stop Lights	
Check Reverse Light(s) & Alarm	
Check ALL Work Lights	
Check Low Air Warning Devices	
Check Rotating Light Operation	

Check Interior Light Operation

Note: ALL items MUST be "Ticked" if carried out / "Crossed" if not carried out / marked "N/A" if not applicable. R = Repair C = Completed RC 250 / 750 Hour Service Continued Comments Check Cabin for Water Leaks Check Seat Mounting & Operation Check Seat Belt Condition & Operation Check Door Locks & Catches for Operation **ENGINE BAY & TRANSMISSION** Clean or Replace Air Filter (Outer Element Only) built up depris around core Visual Inspect Radiator Screen & Cooler Cores for Blockage Check Coolant & Inhibitor Level / Concentration tightened Check ALL Coolant / Heater System Hoses Check for tightness, cracking/splitting Visual Inspect Air Intake Pipes & Hoses Tighten Intake Hose Clamps **Check Fan Coupling** Check Alternator & A/C Compressor Mount/Bolts Check Engine Drive Belt Check Engine Oil Level Check Engine, Lines & Hoses for Abrasion & Position Check Engine Piping for Leaks Visual Inspect Engine Mount(s) Condition Check for Fuel Leaks ALL Points Check for Oil Leaks in Engine Area Check Hydraulic Pump PTO, Mounting & Bolts Serviced Check Transmission Oil Level Replace oil and filter if lower than 30% 23% Check Oil Service Condition Through Gear Selector Pad Replace oil and filter if display is reading (LO) Check Filter Service Condition Through Gear Selector Pad **DRIVE TRAIN & TRANSFER CASE** Check Planetary Reduction (s) Oil Level **Check Transfer Case Oil Level** Run at 1000 rpm for 1 min, then check immediately Check Transfer Case Cooler System for Flow & Leaks Check All Differentials Oil Level Check Susp Cylinder - Condition / Leaks / Positions Check Suspension Cylinder Pivots Check All Suspension Components - wear / tightness Check All Steering Components - wear / tightness / hoses Check centre bearing and housing; Jack Shaft & Front Shaft Check ALL Drive / PTO / Jack Shaft Universal Joints Lube ALL Universal Joints on Drive Line / PTO Shaft Check Wheel Bearing Play Check Brake Lining Thickness / Wear - record thickness 2 mm Minimum Thickness = Minimum Thickness = 37 mm Check brake rotor thickness

		L/H lining outer	inner	R/H lining inner	outer	L/H rotor	R/H rotor
	Axle 1						
	Axle 2						
	Axle 3						
1	Drain AL	L Air Tanks of W	ater / Sedir	nents			
1	Ćheck A	LL Steering Pins	/ Bearings	for Wear			
-	Lube AL	L Steering Pins /	Bearings			Use SBX2 Grease	
1	Tighten :	Steering Pin Bolt	s			Torque setting 420Nm/310lb	o.ft
1	Check S	ervice Brake Ope	ration				
1	Check B	rake Expanding (Cylinders				

QF23Q.03

R = Repair C = C

C = Completed

R	-		
	C	250 / 750 Hour Service Continued	Comments
	/	Check Low Air Warning Devices	
	/	Lube Suspension Cylinder Bearings	Use SBX2 Grease
	~	Check All Covers, Panels for Security	
	/	Inspect steering hoses	As per Service bulletin SB0069
\neg	1	Inspect steering cylinders	
		BOOM ASSEMBLY	*
	1	Adjust ALL Retract & Extension Ropes/Chains	Refer Operator's Manual for Spec.
_		Check 2 nd Extension Cylinder Anchor Pins	
一,	7	Re-tension Tele Secondary Cylinder Hoses	Refer Service Bulletin EAF SA 19 001
7	1	Retension internal secondary cylinder hose fittings	
\top	-	Check Winch Gearbox Oil Level	
+	-	Check Winch Rope Condition & Lubrication	
+	-/	Check Winch Unit Mountings & Bolts & Mounting Hinge	
+	_	Visual Inspection of ALL Boom Sect. Damage/Bend	
1	1	Lube All Boom Sections, Sheaves & Wear Pads	
-	1	Inspect Compensating Sheave Bearings	
+	-	Inspect ALL Sheaves on Boom Assy.	
+	1	Check Boom Rear Pivot Pins/Bearings for Movement	Adjust if required
+	_	Lube Rear Boom Pivot Bearings	Use SBX2 Grease
+	1	Check Luff Cyl. Top/Bott Pins & Bearings Movement	Use SBA2 Glease
+	1	Lube ALL Luff Cyl. Bearings	Use SBX2 Grease
+	1	nspect retract assemble & wear pads	
+	-4	nspect retract assemble a wear paus nspect front side wear pad adjustment & fasteners	remove top inspection hatch cover
+	+	ispect front side wear pad adjustment & fasteners	
		CHASSIS & FINAL CHECKS	
Т	1		Defer Caning Bullatin CD0105 denuite T151016
+	_	Check Center Pivot Bearings/Pins for Movement Check counter weight pins/circlips for correct fitment	Refer Service Bulletin SB0105, drawing T151816
+	/		Use SBX2 Grease
+,	_	ube Centre Pivot Bearings ALL Points	
+	-	Check Hydraulic Reservoir Oil Level	Boom Closed Up (Lowered & Retracted)
+	+	Check Hydraulic Oil Level Sensor Operation	Refer to manual for spec. service
+	+	heck Central Lubrication System	
1/	-	Check Hoist Limit Switch	faulty - replaced
+	/	heck Lower Limit Switch	
+	+	heck ALL Hydraulic Cyl's for Damage/Leaks	
+	/c	heck ALL Hydraulic Hoses for Damage/Leaks	
V	1	heck ALL Wiring for Damage & Correct Routing	
+	1	heck for Air Leaks ALL Points	
1	1	heck Battery Electrolyte Level	
1	/	lean & Check Battery Terminals-Holding Clamp	
1	1	heck Tyre Pressures & Tyre Condition	120psi Front & Back
1	4	arry Out FULL Function/Operate Test Drive	
1	Tr	ransmission Pre-select Downshift to 3rd	
10	CI	heck Exhaust Brake Operation	
+	Li	ft Test Weight if Available	
1			1
\ \ \	CI	heck LMI Calibration	
\ \ \ \	1	e-Tension ALL Wheel nuts	Refer Operators Manual for Tension Settings

R = Repair C = Completed

R	C	500 Hour Service Schedule	Comments
T	/	Carry Out 250 Hour Service Schedule	
		Add the Following:	
T	/	Change Engine Oil Filter	
I	1	Change Engine Oil	
T	1	Change Hydraulic Oil Return Filter	
I	J	Change Transfer Case Oil	
I	\checkmark	Change All Differential Oil	
	/	Change All Planetary Reduction(s) Oil	4
	/	Adjust Rear Boom Pivot Bearings	
	1	Change Winch Gearbox Oil	
T	V	Brakes - Air Dryer - Replace Granulate Cartridge	NOT Applicable on 100 Hour Service

R	C	1000 Hour Service Schedule	Comments
	1	Carry Out 250 / 750 Hour Service Schedule	
	1	Carry Out 500 Hour Service Schedule	
		Add the Following:	
	/	Change Primary (Outer) Air Filter Element	NOT Applicable on 100 Hour Service
\Box	1	Change Safety (Inner) Air Filter Element	NOT Applicable on 100 Hour Service
	1	Replace Fuel Filter Element	
	/	Replace Fuel Pre-filter Element	
		Adjust Valve Clearances	
		Change Cylinder Head Valve Cover Gasket	Refer to Service Manual for Spec.
	J	Check & Clean Engine Breather	
\neg	N	Sample Hydraulic Oil using Kit PP2128300	
	1	Change Auto Transmission Oil and filters	At 1000hrs or when instructed by oil/filter life monitor if sooner,
\neg			Not applicable on 100 Hour Service. Not applicable to
7			transmissions filled with synthetic oil.

R	C	2000 Hour Service Schedule	Comments
	1	Carry Out 250 / 750 Hour Service Schedule	
	1	Carry Out 500 Hour Service Schedule	
	1	Carry Out 1000 Hour Service Schedule	
		Add the Following:	
	1	Change Engine Coolant	
1		Check Wear Pad "Clearance" & Boom Alignment	If Wear is Out Limits Strip & Remove ALL Pads
	1	Check Steering Accumulator Charge Pressure	50 Bar
	/	Check Front Suspension Accumulators Charge Pressure	50 Bar
		Check Rear Suspension Accumulators Charge Pressure	70 Bar

R = Repair C = Completed

	repair C - completed	
R (100 Hour First Service Schedule	Comments
	Carry Out 250 / 750 Hour Service Schedule	
	Carry Out 500 Hour Service Schedule	
	Carry Out 1000 Hour Service Schedule	
	Add the Following:	
\top	Tighten ALL Hose Clamps	
T	Check Tension of ALL Engine mounts	Refer Parts Manual for Tension Settings
	Re-Tension ALL & Suspension Bolts	Refer Operators Manual for Tension Settings
	Re-Tension Centre Pivot Pins - Upper/Lower	Refer Operators Manual for Tension Settings
T	Check & Adjust All Axle Alignment to Centre	Refer to Service Manual
T	Tighten ALL Drive Shaft / Jack Shaft Flange Bolts	

1	1 1	24	
		34 1	

R = Repair C = Completed

R =	Rep	pair	C = Completed
R	C		Additional Faults Identified Continued:
Ц		35	
		36	
		37	
		38	
		39	
П		40	
П		41	
П	1	42	
П	4	43	
	4	44	
	4	45	
	4	46	
	4	17	
	4	18	
	4	19	
	5	0	
	5	1	
	5	2	
	5	3	
	5	4	
	5.	5	
	5	6	
	5	7	
	58	8	
	59	9	
	60	0	
	63	1	
	62	2	

Service carried out by:

Service carried out by:

Signature:

Signature:

QF23Q.03

June 2019

Page 7 of 7